



MA 283 D/S SL

GENERAL TECHNICAL CHARACTERISTICS

Structure: enamelled steel, closed firebox
Firebox: in Aluker®
Fire pit: in cast iron
Hood: in steel
Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Rise n fall door, hinged opening for cleaning
Door profile: in enamelled steel
Door handle: in enamelled steel
Primary air: adjustable manually
Secondary air: fixed
Flue outlet: top
Flue damper: manual
Ash pan: removable
Fuel: wood
Heating: radiant and natural convection

TECHNICAL DATA

Room heating capacity (min-max)	m ³	200 - 345
Nominal thermal efficiency	%	> 70
Rated heat output	kW	12
Consumption at rated heat output	Kg/h	4,5
Maximum heat output	kW	13
Maximum consumption	Kg/h	5,3
Flue outlet	Ø cm	25
Flue up to 4,5 mt*	Ø cm	30
Flue over 4,5 mt*	Ø cm	25
Fresh air intake (recomm. min sect.)	cm ²	300
Weight	Kg	185

ON REQUEST

- Cooking Pro kit
- Adjustable legs kit
- Positioning handles kit

Laboratory data using beech wood with less than 20% moisture content. Consumptions may vary according to the type of wood used



The availability of models may vary from Country to Country.

Compatible Cover

TECHNICAL DRAWING

